

PRE TECH AND DECLARATIONS SHEET

THIS FORM MUST BE PROVIDED TO THE TECH-STEWARD ACCORDING TO THE PUBLISHED TIME SCHEDULE
IT IS THE COMPETITORS RESPONSIBILITY TO CHECK HIS KART FOR COMPLIANCE
ALL RELEVANT AREAS SHOULD BE MARKED BY THE COMPETITOR TO SIGNIFY COMPLIANCE

EVENT LOCATION: _____

DATE: _____

DRIVER NAME: _____

CLASS : _____ KART #: _____

HELMET REQUIREMENTS

Competitor must present a helmet meeting one of the following requirements:

CMR - 2007, CMS - 2007, Snell standards K200510, M2005/10 or SA2005/10. FIA 860-2004
SFI standards 24.1, 31.1A, 31.2A, 31.1/2005, 41.1 and 41.2A. British Standards BS665885, Type A, Type
British Standard - See date of manufactures information inside of helmet, must be within 10 years.

ALL CLASSES MINIMUM REQUIREMENTS

PLACE CHECK IN BOX TO SIGNIFY COMPLIANCE

NUMBERS AND GRAPHICS

Official number, assigned at registration, displayed on front, back and both sides of kart

Required graphic stickers applied to driver fairing/nose

MOUNTING WEIGHTS ON KART CHASSIS

WEIGHTS ARE PAINTED WHITE AND HAVE THE DRIVER NUMBER ON IT

INDIVIDUAL WEIGHTS EQUAL TO OR GREATER THAN 7 POUNDS

2 bolts of minimum 6mm diameter/ Nylock or metal locking nuts, drilled and keyed or double nuts

INDIVIDUAL WEIGHTS LESS THAN 7 POUNDS

1 bolt of minimum 8mm diameter/ Nylock or metal locking nuts, drilled and keyed or double nuts

TRANSPONDER PLACEMENT

Transponder must be mounted in the back of the seat or in a place approved by TECH DIRECTOR during pre-tech.

THE FOLLOWING MUST BE SAFETY WIRED , KEYED, METAL LOCK NUTS OR CLIPS

Fastners / Brake pedal to frame and brake rod ends

Brake control link must be doubled. If cable must be min.1.8mm with secure clamps

Fastners / Brake rotar mounting to hub

THE FOLLOWING MUST HAVE MINIMUM NYLOCK NUTS

Fastners / Brake calipers and master cylinders

Fastners / 3 steering wheel to hub and hub to steering shaft

Fastners / Steering shaft to frame, all tie rod ends, king pins

COMPETITORS UNDER 16 YEARS OF AGE

Competitor must present an SFI Specification 20.1 approved chest protector

SHIFTER CLASS ADDITIONAL REQUIREMENTS

THE FOLLOWING MUST BE SAFETY WIRED , KEYED, OR CLIPPED

Fastners / Front brake calipers and master cylinders

Fastners / 3 steering wheel to hub and hub to steering shaft

Fastners / Steering shaft to frame, all tie rod ends, king pins

KARTS MUST MAINTAIN THESE MINIMUM STANDARDS FOR THE DURATION OF THE EVENT !
FAILURE TO DO SO MAY RESULT IN DISQUALIFICATION !

DECLARED SERIAL / SEAL NUMBERS

Engines must be declared prior to qualifying.

Engine Seal 1 #:

Engine Seal 2 #:

Chassis Seal #:

If a second engine it's not declared the driver will start last on the heat engine is used

PRINTED NAME OF PERSON PREPARING KART / FORM : _____

SIGNATURE OF PERSON PREPARING KART / FORM : _____

THIS FORM MUST BE PROVIDED TO THE TECH-STEWARD ACCORDING TO THE PUBLISHED TIME SCHEDULE